


BREAK SHARP CORNERS MAY BE EITHER CHAMFER OR RADIUS FROM 0.2 mm MIN. TO 1.0 mm MAX.

THIS DRAWING IS A SOLE PROPERTY OF M & M Ltd. IT SHOULD NOT BE REPRODUCED IN ANY FORM OR BY ANY MEANS WITHOUT THEIR CONSENT

REFER DRAWING :- 007537394C91

REF PART NO: 007537394C91

| UNSPECIFIED TOLERANCES AS PER ISO-2768-1:1989 (DIMENSION) |                 |                                            |        |        |        |        |        |      |      |      | SURFACE FINISH SYMBOLS:ISO-1302                                                       |                   |  |      | MAHINDRA & MAHINDRA LTD. |            |                         |  |
|-----------------------------------------------------------|-----------------|--------------------------------------------|--------|--------|--------|--------|--------|------|------|------|---------------------------------------------------------------------------------------|-------------------|---------------------------------------------------------------------------------------|------|--------------------------|------------|-------------------------|--|
| LINEAR<br>IN mm.                                          |                 | OVER                                       | 0.5    | 3      | 6      | 30     | 120    | 400  | 1000 | 2000 | WELDING SYMBOLS:IS813                                                                 |                   |                                                                                       |      | FARM DIVISION, INDIA     |            |                         |  |
|                                                           |                 | UPTO                                       | 3      | 6      | 30     | 120    | 400    | 1000 | 2000 | 4000 | REMOVE ALL SHARP CORNERS & BURRS                                                      |                   |                                                                                       |      |                          |            |                         |  |
| f                                                         | FINE (X.XXX)    |                                            | ±0.05  | ±0.05  | ±0.1   | ±0.15  | ±0.2   | ±0.3 | ±0.5 | -    | DO NOT SCALE<br>ALL DIMENSIONS ARE IN mm                                              | <SC> COUNT : 0    |                                                                                       | NAME |                          | DATE       | PROJECT CODE:           |  |
| m                                                         | MEDIUM (X.XX)   |                                            | ±0.1   | ±0.1   | ±0.2   | ±0.3   | ±0.5   | ±0.8 | ±1.2 | ±2   |                                                                                       | <CC> COUNT : 0    |                                                                                       | DSNR | AR                       | 07-06-2023 | ER NUMBER: ER23C0000228 |  |
| c                                                         | COARSE (X.X)    |                                            | ±0.2   | ±0.3   | ±0.5   | ±0.8   | ±1.2   | ±2   | ±3   | ±4   |                                                                                       | WEIGHT(kg) : 0.15 |                                                                                       | CHKR | NVC                      | 07-06-2023 | DESCRIPTION :           |  |
| v                                                         | VERY COARSE (X) |                                            |        | ±0.5   | ±1     | ±1.5   | ±2.5   | ±4   | ±6   | ±8   |                                                                                       | S/F AREA(cm²): 66 |                                                                                       | APPR | DS                       | 07-06-2023 | ROD CENTER MEMBER       |  |
| ANGULAR<br>IN deg.                                        |                 | LENGTH OF SHORTER SIDE OF THE ANGLE IN mm. |        |        |        |        |        |      |      |      |                                                                                       | MATERIAL:         |                                                                                       |      |                          |            |                         |  |
|                                                           |                 | OVER                                       | -      | 10     | 50     | 120    | 400    |      |      |      |                                                                                       |                   |                                                                                       |      |                          |            |                         |  |
| f                                                         | FINE (X.XXX)    |                                            | ±1°    | ±0°30' | ±0°20' | ±0°10' | ±0°5'  |      |      |      |                                                                                       |                   |                                                                                       |      |                          |            |                         |  |
| m                                                         | MEDIUM (X.XX)   |                                            |        |        |        |        |        |      |      |      |                                                                                       |                   |                                                                                       |      |                          |            |                         |  |
| c                                                         | COARSE (X.X)    |                                            | ±1°30' | ±1°    | ±0°30' | ±0°15' | ±0°10' |      |      |      |                                                                                       |                   |                                                                                       |      |                          |            |                         |  |
| v                                                         | VERY COARSE (X) |                                            | ±3°    | ±2°    | ±1°    | ±0°30' | ±0°20' |      |      |      |                                                                                       |                   |                                                                                       |      |                          |            |                         |  |
|                                                           |                 |                                            |        |        |        |        |        |      |      |      |  |                   | DWG.SIZE : A4                                                                         |      | SCALE : 1:1              |            | SHEET: 1 OF 1           |  |